



DATASHEET

MARANTÉ



KEY FEATURES

- Soft close doors on fall-to-close hinges used to maintain flush appearance
- Available in any HPL or veneer finish or clad with glass, as well as metal and other bespoke finishes.
- 44mm thick hardwood lipped doors with 32mm thick division panels
- Solid stainless steel ironmongery, available in a range of colours
- Full height and made to measure
- Versatile can be installed in conjunction with dividing stud partition walls









MARANTÉ HPL

Specifications

DIVISIONS

Core material: 30mm high grade particle board 650kg/m³ supplied in two parts.

Colour/ Finish: High pressure laminate as per client choice giving 32 mm overall panel thickness.

Edge treatment: All edges lipped in impact-resistant ABS with polyurethane adhesive (see below).

Adhesive Type: All components are bonded with specialist polyurethane washroom adhesive, for ultimate water-resistance and strength of bonding. This adhesive is environmentally friendly with its zero rating on formaldehyde emissions.

FIXING

Division to rear wall: Aluminium T-section fixed into pre-grooved division.

Division to pilaster: Concealed high-strength mechanical fixings.

Division/pilaster to floor & ceiling: Aluminium powder coated channel secured to floor. Division is pre-grooved and placed over the channel, raising it by 20mm and preventing contact with mopping water.

End Pilaster to wall: Fully adjustable aluminium shadow detail.



DOORS / OVER-DOOR PANELS & PILASTERS

Core material: 44mm high grade particle board 650kg/m³.

Colour/Finish: High pressure laminate as per client choice giving 44mm overall panel thickness.

Edge treatment: Rebated vertical edges lipped in 20mm hardwood with 10mm hardwood to horizontal edges. All over-laminated to conceal lipping. Above-door-panel option available on request.

IRONMONGERY

Hinges: Solid stainless steel Butt hinges (fall to close)

Indicator bolt: Solid stainless steel mortise lock with lever operated turn action.

Damper: Hidden hydraulic soft close mechanism to all doors

Internal fixings: Buffered coat hooks in stainless steel.

External fixings: Stainless steel pull handle to outward opening doors.

Tectus concealed hinges and/or ironmongery to be PVD coated in range of colours available on request.

SIZE

Overall height: To suit ceiling heights up to 3000mm

Division (h x w): To suit ceiling height x 1500mm

Door: (h x w): To suit ceiling height x site dimensions

Centre pilasters (h x w): To suit ceiling height x site dimensions

End pilaster (h x w): To suit ceiling height x site dimensions (min. width 100mm)

CARBON NEUTRAL

This product can be fully carbon neutral due to our Climate Partners offsetting scheme.







MARANTÉ REAL WOOD VENEER

Specifications

DIVISIONS

Core material: 44mm high grade particle board 650kg/m³.

Colour/ Finish: Real wood veneer as per client choice with two coats of PU lacquer.

Edge treatment: Rebated vertical edges lipped in 20 mm hardwood with 10mm hardwood to horizontal edges. All over-veneered to conceal lipping. Above-door-panel option available on request.

DOORS & PILASTERS

Core material: 44mm high grade particle board 650kg/m3.

Colour/Finish: Real wood veneer as per client choice with two coats of PU lacquer.

Edge treatment: Rebated vertical edges lipped in 20mm hardwood with 10 mm hardwood to horizontal edges. All over-veneered to conceal lipping.

Above-door-panel option available on request.

FIXING

Division to rear wall: Aluminium T-section fixed into pre-grooved division.

Division to pilaster: Concealed high-strength mechanical fixings.

Division/pilaster to floor & ceiling: Aluminium powder coated channel secured to floor. Division is pre-grooved and placed over the channel, raising it by 20mm and preventing contact with mopping water.

End Pilaster to wall: Fully adjustable aluminium shadow detail.

IRONMONGERY

Hinges: Solid stainless steel Butt hinges (fall to close).

Indicator bolt: Solid stainless steel mortise lock with lever operated turn action.

Damper: Hidden hydraulic soft close mechanism to all doors.

Internal fixings: Buffered coat hooks in stainless steel.

External fixings: Stainless steel pull handle to outward opening doors.

Tectus concealed hinges and/or ironmongery to be PVD coated in range of colours available on request.

SIZE

Overall height: To suit ceiling heights up to 3000mm

Division (h x w): To suit ceiling height x 1500mm

Door: (h x w): To suit ceiling height x site dimensions

Centre pilasters (h x w): To suit ceiling height x site dimensions

End pilaster (h x w): To suit ceiling height x site dimensions (min. width 100mm)

CARBON NEUTRAL

This product can be fully carbon neutral due to our Climate Partners offsetting scheme.



Note: Anything that isn't defined on this standard specification will incur additional costs.



MARANTÉ GLASS

Specifications

DIVISIONS

Core material: 30mm high-grade particle board (650 kg/m³).

Colour/ Finish: High pressure laminate, resulting in 32mm overall panel thickness

(Option for glass to also be applied to division if required, giving 48mm thickness).

Edge treatment: All edges lipped in impact-resistant ABS with polyurethane adhesive (see below).

DOORS / OVER-DOOR PANELS & PILASTERS

Core Material: 42mm high grade particle board (650 kg/m³) laminated with High pressure laminate, resulting in 44mm overall panel thickness.

Colour/Finish: Cubicle fronts are faced with 6mm, back painted, toughened glass giving 52mm overall panel thickness. (Option for glass to also be applied to rear of doors and pilasters if required, giving 60mm thickness).

Edge Treatment: All edges lipped in 20mm hardwood and painted/lacquered, including rebated vertical edges; lipping applied using polyurethane adhesive (see below). All glass edges are bevelled and polished.

Adhesive Type: All components are bonded with specialist polyurethane washroom

adhesive, for ultimate water-resistance and strength of bonding. This adhesive is

environmentally friendly with zero rating formaldehyde emissions.

SIZE

Overall height: To suit ceiling heights up to 3000mm.

Division (h x w): To suit ceiling height x 1500mm.

Door: (h x w): To suit ceiling height x site dimensions.

Centre pilasters (h x w): To suit ceiling height x site dimensions.

End pilaster (h x w): To suit ceiling height x site dimensions (min. width 100mm).

FIXING

Division to rear wall/IPS: Aluminium T-section which locates into pregrooved division

and is screwed into face of wall/IPS.

Division to pilaster: Concealed high-strength mechanical fixings.

Division/pilaster to floor & ceiling: Aluminium powder coated box-section fixed to floor and ceiling. Division is pre-grooved and placed over the box-section. Division remains raised 20mm AFFL, preventing contact with water.

End Pilaster to wall: Adjustable aluminium shadow detail.

Over door panel (if required): Located using secret bayonet duo fixings.

IRONMONGERY

Hinges: Solid stainless steel Butt hinges (fall to close).

Indicator bolt: Solid stainless steel mortise lock with lever operated turn action. Soft

close mechanism to all doors.

Internal fixings: Buffered coat hooks in stainless steel.

External fixings: Stainless steel pull handle to outward opening doors.



Note: Anything that isn't defined on this standard specification will incur additional costs.





AND NOT ONLY THAT,

WE'VE GONE GREEN.





















020 3657 7615



inspired@maxwoodwashrooms.com



www.maxwoodwashrooms.com



Maxwood Washrooms 121-131 Rosebery Avenue London EC1R 4RF

GET IN TOUCH

